

GARAGETUFF: GARAGE FLOOR SYSTEM



DESCRIPTION

Fusion Coatings MMA GarageTuff Garage Floor System is hard wearing, durable, UV stable and 100% seamless and resistant to tyre marks. Fusions MMA resin can be applied to Garage floor substrates to create a decorative easy to clean but durable floor coating.. The special recycled PVC coloured flakes and Quarts aggregate create aesthetically pleasing floors that are very hard wearing.

WHERE TO USE

- Garages
- Workshops
- Home gyms and yoga studios
- Home offices
- Utility/laundry rooms
- Outbuildings and Garden Rooms
- Salons and beauty rooms
- Pet boarding and grooming

BENEFITS OF THE SYSTEM

- Dries and Cures in less than 1 hour
- 100% Seamless (no sealants which fail very quickly)
- Naturally hygienic, kills bacteria (see test results)
- No sealants required around drains and gullies
- UV Resistant
- Waterproof
- No fading colour
- Flexible
- Ideal for high temperatures over 100°C (Warm Tyres)
- 25 year guarantee including the application

TECHNICAL PROPERTIES

PROPERTY	STANDARD TEST METHOD	RESULT
Tensile Strength	DIN EN ISO 527	18 MPa
Compressive Strength	DIN EN ISO 604	48 MPa
Elongation at Break	DIN EN ISO 527	2.3 %
Elastic Modulus	DIN EN ISO 527	2120 MPa
Impact Strength	EN ISO 6272	8 Nm
Wear Resistance	PrEN 13892-4	<10 um
Slip Resistance	BGR 181 and	R9 to R11
Water Absorption	DIN51130 ASTM	<0.1%
Physical Inoffensiveness	D570 EU Regulations 1935/2004	Test Report Number 26049 U 08 the coating system is physiologically safe, suitable for food processing companies.

APPLICATION GUIDE

Can be applied over the following substrates

- Concrete
- Screeds including self-level screeds
- Ceramic Tiles
- Wood
- Metal, Steel,
- Old Failed Resins (Epoxy, Polyurethanes)

Method of application: Rubber Squeegee, Rollers,

Pot Life: 7-15 minutes

Min Re-Coat: 20-30 minutes

Max Re-Coat: NONE

Fully Dried and Cured: 1 hour (60 minutes)

HEALTH & SAFETY

- Always wear appropriate PPE including Gloves, Goggles, Safety Boots, Hard Hat, Reflective Vest and Barrier cream to avoid contact with the skin
- Ensure adequate ventilation or suitable respiratory equipment, use face masks if working in confined spaces
- NO VOC'S or Isocyanates are in our systems and are non-harmful to aquatic life
- Do Not Expose to Naked Flames or Fire during application

Please refer to the MSDS sheets for further information.

CONTACT US

Office: The Atrium,1 Harefield Rd, Uxbridge UB8 1JR
Call: 0208 003 0223
E-mail: sales@fusionresins.co.uk
Online: www.fusionresins.co.uk